

radiomatic® photon



Pricing information

Scope of delivery:

- ✓ Transmission unit radiomatic® photon
- ✓ Operating instructions radiomatic® photon
- ✓ 10 m cable for connection of radiomatic® photon transmission unit to the power supply (10 – 30 V DC / 100 – 240 V AC)
- ✓ Shock mounts for installation of radiomatic® photon transmission unit
- ✓ Orlaco camera:
 - ❖ FAMOS (available with different aperture angles)
 - ❖ FAMOS IR LED 80° (infrared)
 - ❖ CCC stainless steel (IP69K) 102° (increased protection class)
 - ❖ other camera models available on request
- ✓ Further accessories optionally available



Transmission unit
radiomatic® photon

radiomatic® photon – your complete prices:



with Orlaco camera FAMOS
(standard version)

1,570 EUR



with Orlaco camera FAMOS
IR LED 80° (infrared)

1,840 EUR



with Orlaco camera CCC
stainless steel (IP69K) 102°
(higher protection class)

1,995 EUR

Opening offer:

For the delivery of at least 5 radiomatic® photon sets until 31 December 2017, you will receive an additional opening discount of 10 % on the gross price for all sets delivered until this day.

Notes:

- ✓ All prices are gross prices (excluding VAT and shipping) and are valid until 31 December 2017.
- ✓ radiomatic® photon is available in combination with the HBC radio transmitters technos 2, technos B (in preparation) and spectrum E.
- ✓ The suitable HBC radio systems (transmitter and receiver) are available at the known conditions according to the current HBC price list.
- ✓ Retrofitting of an existing HBC radio system with radiomatic® photon is possible if the radio transmitter already supports the use of our current radiomatic® photon generation.

Last revision: 01 December 2016